

MT-300 and MT-600 HOT TACK SPRAYERS

- **Hydraulically Driven Asphalt Pump with Forward and Reverse Material Flow**
- **Reverse Suction Reclaims Material from System**
- **Two Position Optional Spray Bar with Cab Control Allows Outer Nozzel View from Tow Vehicle Mirror**
- **Tank Recirculate Valve**
- **Single, 8" Diameter Flue with Triple Tank Pass**
- **Optional Features:**
 - Diesel Burner with Thermostat Control**
 - Tank Insulation**



****Optional Equipment Shown****

TACK TANKS

WEIGHTS		Model MT-300	Model MT-600
Operating, Tank Empty	2250 lbs / 1,020 kg	2,850 lbs / 1,290 kg	
Torsion Spring Axle(s)	Single	Dual	
Axle Capacity	6,000 lbs / 2,722 kgs	6,000 lbs / 2,722kgs each	
Capacity	300 Gal / 1,135 L	600 Gal / 2,270 L	
DIMENSIONS			
Overall Length	169" / 430 cm		
Overall Width	96.5" / 245 cm		
Loading Height	62" / 158 cm	70" / 178 cm	
Tires	225/75R15		
Brakes	Electric, Single Axle		
PERFORMANCE DATA			
Asphalt Pump	8 GPM / 30 LPM, Reversible		
	Hydraulic Driven		
Heating, Type	Propane, Twin Burners		
Heating Flue	Diameter: 8" / 20cm		
	Single Flue Tube with Triple Tank Pass		
Hand Spray Wand	Single Nozzle		
Hand Spray Hose	40 Feet / 12 Meters		
Hand Spray Hose Reel	Manual Wind		
OPTIONAL SPRAY BAR DATA			
Asphalt Pump	35 GPM / 130 LPM, Reversible		
	Hydraulic Driven		
Width	8 Feet / 2.44 Meters		
Controls	In-Cab Controls		
Thermometer Type	Dial Thermometer, 50° - 550° Fahrenheit		
TANK CONSTRUCTION		Model MT-300	Model MT-600
Tank Heads		Dished & Flanged, Welded Inside & Out	
Tank Shell		Standard Oval Cross Section	
Baffle		NA	with Crawl Hole
Manhole		20" / 51cm	
Contents Gauge		Yes	
ENGINE			
Fuel Type		Gasoline	
Power		9.5 HP (SAE/1394)	
		7Kw	
Type and Cooling		1 Cylinder - Electric Start, Air Cooled	
FLUID CAPACITIES			
Solvent Tank		5 Gal. / 19 L	
Hydraulic Tank		5 Gal. / 19 L	
Diesel Tank, (if equipped)		5 Gal. / 19 L	
TRAILER, SAFETY			
Hitch, Pintle Eye		2 ¾" / 70mm	
Braking		Electronic Break-Away System with Safety Chains	
Wiring		Trailer Lighting, Standard	
OPTIONAL EQUIPMENT			
Skid Mounting, Ball Hitch in lieu of Pintle Eye, Fire Extinguisher, Diesel Fired Burner with Thermostatic Control, Tank Insulation, 110 volt Overnight Heat,			
Non-Recirculating Spray Bar, Joint Spray Nozzle, Pencil Thermometer,			
9.8 HP/ 7.3Kw Diesel Engine, Special Paint			

Mar-13

Calder Brothers Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacture at any time without notice or obligation.

Sold & Serviced by:



Calder Brothers Corporation
250 E. Warehouse Ct.
Taylors, SC 29687
Phone (864) 244-4800
Fax (864) 244-5007
www.CalderBrothers.com